QIANLI
HEBEI QIANLI RUBBER PRODUCTS CO.,LTD

High Pressure Steam Hose



The high pressure steam hose is designed for the transfer of steam within many applications, such as fire prevention, heat control and industries where steam must be transferred safely and reliably. High-pressure steam hose with oil resistant cover : specially developed for saturated steam transfer and for steam cleaning of tanks and pipelines in the chemical and petrochemical industry. It is resistant to bursting, cracking and crushing even under accidental exposure to flame, while being quite flexible and resistant to vibration. It is consist of black, smooth, EPDM rubber especially compounded to withstand super heated steam. It is covered with smooth black weather and abrasion and reinforced with piles of carbon steel wire.

Tube: Black, smooth, EPDM rubber especially compounded to withstand super heated steam

Reinforcement: Multiple braids of hightensile steel wire.

Cover: Red, smooth (wrapped) EPDM rubber with excellent resistance to high temperature, weather, abrasion and aging. It is pin-pricked to prevent separation.

Temperature: -40 °C to +236 °C(-40 °F to +456°F)

Specifications: ISO 6134-TYPE 2 CLASS B

W/B	I.D		O.D.	Working Pressure		Burst Pressure		Minimum B.R	Weight	Length
	DN	inch	mm	Bar	Psi	Bar	Psi	mm	kg/m	metres
1W	10	3/8	21.5	30	435	120	570	110	0.44	20/ 50
	13	1/2	24.5	30	435	120	570	120	0.49	20/ 50
	16	5/8	27.5	30	435	120	570	155	0.64	20/ 50
	19	3/4	30.5	30	435	120	570	185	0.7	20/ 50
	25	1	37	30	435	120	570	240	0.92	20/ 50
	32	1 1/4	44	30	435	120	570	330	1.19	20/ 40
	38	1 1/2	50.5	30	435	120	570	390	1.56	20/ 40
	51	2	63.5	30	435	120	570	520	2.32	20/ 40
	64	2 1/2	77.5	30	435	120	570	640	3.03	20/ 40
2W	10	3/8	23	70	870	280	860	130	0.49	20/ 50
	13	1/2	26	70	870	280	860	180	0.53	20/ 50
	16	5/8	30	70	870	280	860	205	0.75	20/ 50
	19	3/4	33	70	870	280	860	240	0.78	20/ 50
	25	1	40	70	870	280	860	300	1.02	20/ 50
	32	1 1/4	48	70	870	280	860	420	1.41	20/ 40
	38	1 1/2	54	70	870	280	860	500	1.77	20/ 40
	51	2	69	70	870	280	860	630	2.58	20/ 40
	64	2 1/2	81	70	870	280	860	700	3.16	20/ 40

Tina Zhao / Sales Manager

Mobile: +86-18632062856 **Fax**: +86-318-666 8207 **Skype:** qianlisales@hotmail.com **Email:** tina@hebeiqianli.com

Web: www.hebeiqianli.com **Address:** West Industrial Zone, Jing County,Hengshui City, Hebei Province, China

QIANLI
HEBEI QIANLI RUBBER PRODUCTS CO.,LTD

Ground Joint Fittings(Boss Coupling)

Spud (GJFS)	Swivel nut	Female stem	Full set	Male stem	sizes
					1/2"
					3/4"
					1"
					1-1/4"
					1-1/2"
					2"
					2-1/2"
					3"
					4"

Clamps / Interlock

2 Bolts	4 Bolts	Sizes available
		1/2"
		3/4"
		1"
		1-1/4"
		1-1/2"
		2"
		3"

Tina Zhao / Sales Manager
Mobile: +86-18632062856 **Fax**: +86-318-666 8207 **Email:** tina@hebeiqianli.com
Web: www.hebeiqianli.com **Skype:** qianlisales@hotmail.com
Address: West Industrial Zone, Jing County,Hengshui City, Hebei Province, China